

ABU FEEL

POLYESTER - RESIN BASED MASTICS FOR MARBLE, GRANITE, STONES - MASTICE POLIESTERE PER MARMO, GRANITO, PIETRA - مواد من جلودىس للزئيق لك انواع ارحام الجوانيت، الاحجار

Use Instructions:
This mastic is not the substitute of cement and it is not 100% of the repair material. The mastic must be applied on dry and clean surface and should be applied in dry and clean surface. It is highly resistant to water and the mastic should be applied in a thin layer.

Preparation of the surface:
The surface to be treated must be clean, dry and free from any oil, dirt, dust, etc. The surface should be roughened by sandpaper or by any other means. The surface should be clean and dry before the application of the mastic.

Application:
Apply the mastic on the surface to be treated with a brush or trowel. The mastic should be applied in a thin layer and should be smoothed with a trowel or brush. The mastic should be applied in a thin layer and should be smoothed with a trowel or brush.

Precautions:
Avoid contact with the eyes and skin. In case of contact, wash immediately with water. Do not use on electrical appliances. Do not use on surfaces that will be in contact with water.



ABU FEEL

أبو فيل

1Kg e

CONTENE STROLO

R-10 Infiammabile - Inflammable - Inflammable
R-20 Nocivo per inalazione - Dangerous if inhaled
R-36 Irritante per l'irritazione
R-37 Irritante per le vie respiratorie - May cause inflammation to respiratory tract - Irritant pour les voies respiratoires
R-38 Irritante per la pelle - Skin-irritating - Irritant pour la peau
S-10 Conservare lontano da fiamme e fonti di calore - Keep away from fire and sparks. Do not smoke.
S-23 Conservare il prodotto lontano da bambini - Keep the product away from children.

NON CONTIENE BENZOLE - TOLUOLI - XILOLI - DOES NOT CONTAIN BENZOL, TOLUOL, XYLENE

MADE IN ITALY
bulldexp@globalshipping.it

ACC 

100% garantito 100% professional

AL THURAYA

ATTENZIONE:
Falcone del brandito la qualità superiore per l'uso in esterno.
Application Falcone in esterno deve essere in un ambiente asciutto e riparato dall'umidità.
Before it is used in outdoor applications it must be used in a dry and protected environment.
Questo prodotto è adatto per l'uso in esterno e in ambienti umidi.
This product is suitable for outdoor use and in humid environments.
Add the hardener/catalyst in the necessary quantity for the immediate use.
Add the hardener/catalyst from 15% to 10% depending from the class of employment required and tested with care.
Add the level the amount of the hardener/catalyst with the use of AL THURAYA.
Keep the tin well closed and in cool place.

ACC 

750 ml. e



AL THURAYA

MASTICE PER MARMO, GRANITO, PIETRA
MASTICS FOR MARBLE, GRANITE, STONES

MADE IN ITALY

NUOVO

CONTENE STROLO

R-10 Infiammabile - Inflammable - Inflammable
R-20 Nocivo per inalazione - Dangerous if inhaled
R-36 Irritante per l'irritazione
R-37 Irritante per le vie respiratorie - May cause inflammation to respiratory tract - Irritant pour les voies respiratoires
R-38 Irritante per la pelle - Skin-irritating - Irritant pour la peau
S-10 Conservare lontano da fiamme e fonti di calore - Keep away from fire and sparks. Do not smoke.
S-23 Conservare il prodotto lontano da bambini - Keep the product away from children.

NON CONTIENE BENZOLE - TOLUOLI - XILOLI - DOES NOT CONTAIN BENZOL, TOLUOL, XYLENE

MADE IN ITALY

FALCON

FALCON

GOLDEN FALCON

Made in Italy

HIGH RESISTANT GLUE FOR MARBLES GRANITES AND STONES

HIGH KNIFE GRADE. POLISHING TO HIGH GLOSS.

How to use:
The surface must be dry, dust and grease free and possibly slightly roughened. The mastic can be coloured by special colouring pastes for polyester mastic (max 5%). Mix carefully 100 gr. of mastic together with 2-4 gr. of hardener/catalyst. The obtained mixture is workable, at a temperature of 20°C (68°F), for about 8 to 6 minutes. After other 30 to 60 minutes (at 20°C / 68°F) the cured mastic can be worked (drilled, grinded, polished).

CAUTION: Keep the hardener/catalyst far from the eyes and avoid the contact with the skin.

Only for professional use.
Always test the product before use.

Made in Italy


HIGH RESISTANT GLUE FOR MARBLES GRANITES AND STONES

FALCON

GOLDEN FALCON

Made in Italy

HIGH RESISTANT GLUE FOR MARBLES GRANITES AND STONES

ACC 

19 L e

HARDENER FOR MASTIC - P60



Sizes available:

(Tube or Jar) 5ml - 20gr - 30gr - 100gr - 130gr - 500gr - 600gr - 750gr - 5kg - 25kg

EXTRA DROP: WET LOOK

EXTRA WAX: SOLVENT BASE

DRAI: WATERPROOF SEALANT

BRILLO: LIQUID SILICON BASED WAX

EXTRA LUX: SELD POLISHING VARNISH



1901 - NITRO THINNER EXPORT

Low-cost nitro thinner particularly suitable for thinning primers for use on wood and iron.
A good product for washing painting tools



Tins Available:
1lt – gallon – 5lt – 9lt – 17lt – 25lt

ADHESIVE RESIN SOLUTION



USES :
Leather - Wood - Formica - Foams - Rubber

Size Available :
Tin 250gr - Tin 500gr - Tin 600gr - Tin 1kg - Tin 2.5kg - Tin 3kg - Tin 3.5kg

WICTOR ULTRA-FIX is a strong, quick-setting adhesive; very resistant to high temperatures. Suitable for bonding plastic laminates (e.g.: formica), carpet, foam rubber, leather, synthetic leather, and hide to each other or to rigid materials, (e.g.: wood, refined or unrefined sheet metal, plastic, etc.). Also suitable for several bonding applications in the Shoe Industry.

CEMENT BASED POWDER ADHESIVE FOR CERAMIC TILES



CHARACTERISTICS

For interior floor and wall coverings / tile absorption > 3%.

Composition: cement, siliceous sand, syntetic resin and additives.

Consistency: granular powder.

Expiry: 12 months in original packing if kept in dry place.

Packaging: 20kg bags.

Powder adhesive made up of grey or white cements, aggregates with chosen granulometry and special additives. Its formula is the result of years of experience and guaranteed by thousands of applications in Italy and abroad each year. Mixed with water, EASY TILE / TILEFIX becomes a shiny plastic paste with good adhesive qualities for all floor and wall covering materials with absorption $\geq 3\%$ and for all sub-bases that are normally used in construction.



BENFERFLEX C2

Fiber reinforced flexible adhesive

- High flexibility
- No vertical sliding
- Ideal for exterior application
- Ideal for porcelain stoneware
- Ideal for large sizes
- Application thicknesses up to 15 mm
- Tested in accordance with EN 12004, C2 TE S1

TECHNICAL FEATURES:

BENFERFLEX C2 is a thixotropic flexible adhesive formulated and developed for rapid, reliable installation of porcelain tile and ceramic tile on cement based screeds, non-absorbent substrates



BENFERGRIP +

Special adhesive created to prevent vertical slippage of tiles when fixing, High strength and long open time

- Extra-white
- High resistance to sliding
- Application without the need for spacers
- Perfect for glass and ceramic mosaics
- Long open time
- Conforms to: EN 12004 CLASS C2TE
- With CEMLATEX 600 Conforms to: EN 12004 CLASS C2TE S2

TECHNICAL FEATURES:

BENFERGRIP + is a HIGHLY TIXOTROPIC powder adhesive conceived and developed for rapid and safe installation of all ceramic materials, even from top to bottom.

SPECIAL GROUT FILLER FOR CERAMIC TILE & JOINTS



PRIMA FUGA

Grouting of joints between ceramic floor and wall tiles of all types and sizes, both indoors and outdoors.

Grain available : 0/0 - 0/5 - 2/12 - 5/15

CHARACTERISTICS:

Colour: 20 Colors available

Composition: Cement, Synthetic resin, calcium filler, additives

Consistency: Granular powder

Expiry: 6 months in original packages if kept in dry place

Packaging: Fine grain 5 - 20kg bags / Coarse grain 25 - 5kg bags



CEMLATEX GIUNTI

Cement joints latex

Its characteristics united with those of Benfer grouts created brilliant solutions to joint filling problems in:

- systems that are subject to slight dimensional variations;
- wall and floor coverings subject to harsh environmental conditions such as swimming pools, walk-in refrigerators, terraces and surfaces very exposed to water;
- floors located in heavily trafficked areas such as supermarkets, highway rest stops, malls, and public places in general;

It is a polymeric dispersion additive for Benfer cement joint grouts to improve elasticity, waterproofing, mechanical resistance and adhesion.



DEKOGROUT

Antibacterial, flexible, smooth cement-based grout

- Antibacterial and mould resistant
- Water repellent
- Resistant to freeze/thaw cycles
- Smooth surface and wide colour range, 24 colours
- For interior, exterior and under water
- Fulfils the requirements of EN 13888, CG2WA
- For joints from 1 – 6 mm wide
- EC1R: very low emission

DEKOGROUT is suitable for grouting glass mosaic, vitrified and fully vitrified clay tiles, brick tiles, tile slips, floor clinkers in bathrooms, showers and living rooms, on terraces, balconies and loggia. As well as facades, in swimming pools, commercial areas, and on heated and flow screeds.



ADDITIVES & LATEXES



ACQUASHIELD +

Flexible, two-component mortar for waterproofing application. balconies, terraces, swimming pools and concrete structures

TECHNICAL FEATURES:

ACQUASHIELD + is a highly resistant cement-based bi-component mortar with fine quartz, new generation additives (component A) and high tech synthetic polymers in water dispersion (component B).

It can be easily applied with a roller, brush and trowel, for horizontal and vertical application.

It has been formulated and developed to protect cement-based plasters and concrete structures - including those in contact with the ground, such as exterior cement-based screed on terraces, balconies and swimming pools - against premature ageing caused by the action of water, salts and frost.



CEMLATEX 600

SYNTHETIC LATEX FOR THE PREPARATION OF MORTARS

- Transforms a good adhesive into a superior quality adhesive
- Gives adhesives an extremely high flexibility
- Ideal for large size applications
- Gives very high adhesion and elasticity to cement-based mortars
- Permits long lasting concrete pouring
- Reduces the absorption of water

WALLPAPER ADHESIVE METHILCELLULOSE ETHER



GLUE PREPARATION:

Empty entire contents of packet at once while stirring water vigorously. Leave for 5 minutes and stir again.

USE:	DILUTION:	ROLLS N°:
NORMAL WALLPAPERS	9 Lt	9
HEAVY WALLPAPERS	8 Lt	8
VERY HEAVY WALLPAPERS	6 Lt	6

WOODEN HANDLES



PAPEREMOVER

Special remover for wall paper, wall painting and washable coverings

APPLICATION

- 1) Concentrated for the removal of any kind of wall paper
- 2) Removal of washable wall painting

CONSUPTION

Dilute the package in 8 litres of water (about 40 sq m)



ADHESIVA 2 P/G

Two components epoxy polyurethane adhesive for parquets and rubber floors. Low voc emission

APPLICATION

- 1) Traditional and prefinished wood floors of any kind and size
- 2) Rubber indoor floors in sheets and square tiles
- 3) PVC floor coverings

CONSUPTION

800 - 1000 g/sq m



GLASTER - GLASTER D

Extralight filling plaster with thermo-insulating properties. Does not shrink nor cracks, ready for use. does not require flatting

APPLICATION

- 1) Fit for filling holes, cracks, fissures, missing parts on walls and wood
- 2) For thickness from 1mm up to 5 cm
- 3) The product does not shrink nor crack, ready for use; it does not require flatting
- 4) Restores walls ruined by humidity and has thermo-absorbent effects
- 5) The product can be coated with any kind of painting or water enamel
- 6) Exceptional for plastering polystyrene and polyurethane frames and roses and to fill plasterboard gaps
- 7) Extra white with excellent yield

CONSUPTION

According to filling thicknesses



the 1990s, the number of people in the UK who are employed in the public sector has increased from 10.5 million to 12.5 million, and the number of people in the public sector who are employed in the health sector has increased from 2.5 million to 3.5 million (Department of Health 2000).

There are a number of reasons for this increase in the number of people employed in the public sector. One of the main reasons is the increasing demand for public services, particularly in the health sector. The population of the UK is increasing, and the number of people who are aged 65 and over is increasing rapidly. This has led to an increase in the number of people who are dependent on public services, particularly in the health sector.

Another reason for the increase in the number of people employed in the public sector is the increasing demand for public services in other sectors, such as education and social care. The number of people who are employed in the public sector in these sectors has also increased in the 1990s. This is due to the increasing demand for public services in these sectors, particularly in the area of social care.

There are a number of reasons for the increase in the number of people employed in the public sector in the health sector. One of the main reasons is the increasing demand for health services, particularly in the area of primary care. The number of people who are employed in the public sector in the health sector has increased in the 1990s due to the increasing demand for health services in this area.

Another reason for the increase in the number of people employed in the public sector in the health sector is the increasing demand for health services in other areas, such as hospital care and specialist services. The number of people who are employed in the public sector in the health sector in these areas has also increased in the 1990s. This is due to the increasing demand for health services in these areas.

There are a number of reasons for the increase in the number of people employed in the public sector in the health sector in the area of primary care. One of the main reasons is the increasing demand for primary care services, particularly in the area of general practice. The number of people who are employed in the public sector in the health sector in the area of primary care has increased in the 1990s due to the increasing demand for primary care services in this area.

Another reason for the increase in the number of people employed in the public sector in the health sector in the area of primary care is the increasing demand for primary care services in other areas, such as community health centres and health centres. The number of people who are employed in the public sector in the health sector in the area of primary care in these areas has also increased in the 1990s. This is due to the increasing demand for primary care services in these areas.

There are a number of reasons for the increase in the number of people employed in the public sector in the health sector in the area of primary care in the area of general practice. One of the main reasons is the increasing demand for general practice services, particularly in the area of family medicine. The number of people who are employed in the public sector in the health sector in the area of primary care in the area of general practice has increased in the 1990s due to the increasing demand for general practice services in this area.